

## Time-lapse seismic tomography using the data of microseismic monitoring network in Pyhäsalmi mine (Finland)

J. NEVALAINEN<sup>1\*</sup>, AND E. KOZLOVSKAYA<sup>2</sup>

<sup>1</sup>*Sodankylä Geophysical Observatory, Laboratory of Applied Seismology, BOX 3000, University of Oulu, FIN-90014, University of Oulu, Finland*  
(\*correspondence : jouni.nevalainen@oulu.fi)

<sup>2</sup>*Oulu Mining School, BOX 3000, University of Oulu , FIN-90014, University of Oulu, Finland*

We present results of a seismic travel-time tomography applied to microseismic data from the Pyhäsalmi mine, Finland. The data about microseismic events in the mine is recorded since 2002 when the passive microseismic monitoring network was installed in the mine. Since that over 100000 microseismic events have been observed. One of the purposes of our study was to test how the travel-time tomography works with the passive microseismic monitoring data where the source-receiver geometry is based on non-even distribution of natural events in the mine and hence, is a non-ideal one for the travel-time tomography. The tomographic inversion procedure was tested with the synthetic data and real source-receiver geometry and with the real travel-time data of the first arrivals of P-waves from the microseismic events. The results showed that seismic tomography is capable to reveal differences in seismic velocities in the mine area corresponding to different rock types, for example, the velocity contrast between the ore body and surrounding rock. The velocity model recovered corresponds well to the known geological structures in the mine area. The second target was to apply the travel-time tomography to microseismic monitoring data recorded during different time periods in order to track temporal changes in seismic velocities within the mining area as the excavation proceeds. The result shows that such a time-lapse travel-time tomography can recover such changes. In order to obtain good ray coverage and good resolution, the time interval for a single tomography round need to be selected taking into account the number of events and their spatial distribution.

Acknowledgements: This study has been supported by ERDF SEISLAB project and Pyhäsalmi Mine Oy.